



TECHNICAL DATA

| | |
|----------------------|---|
| Cycle times (*) | 60 / 90 / 180 sec. and special cycles |
| Water consumption | Upper Level: 2,0 l / rack Lower Level: 2,5 l/rack |
| Tank capacity | 30 l |
| Tank heating | 3 kW |
| Power supply | 415 / 50 / 3N |
| Booster loading | |
| Standard | 9,1 kW |
| Total loading | |
| Standard | 13.6 kW 3 x 25A |
| Alternative | 10.4 kW 3 x 20A |
| Wash pump | 1,2 kW |
| Rack size | 500 x 500 mm |
| Loading height | Upper Level: 440 mm Lower Level: 235 mm |
| Noise level | 70 dB (A) |
| Weight (gross / net) | 160 / 140 kg |

PRODUCT ADVANTAGES

- **Double capacity:** The TLW provides twice the capacity of a conventional hood-type dishwasher, thanks to an additional wash chamber - but with the same space requirement
- **Maximum flexibility:** Simultaneous washing of different wash ware, such as porcelain dishes, cutlery or cooking utensils, in two separate wash chambers
- **Space saving wash organisation:** For heavily soiled wash ware, the TLW has a special utensil wash programme. Due to the extended washing time, the pre-soaking effect is already integrated into the washing process, so that the wash ware no longer need to be pre-soaked. This saves valuable space in the kitchen organisation
- **VISIOTRONIC-TOUCH control:** colour touchscreen (displays text and graphic) in conjunction with single-button control and remaining cycle time indication
- **WASHSMART app:** controlling your warewash operation with smart technology: status and messages, usage and operating costs, hygiene, service and consumables order
- **SENSO-ACTIVE resource management:** constantly measures the quality of the wash water and keeps the amount of rinsing needed in each rinse cycle to the minimum in order to guarantee a fully hygienic wash result
- **Exhaust energy storage:** the fully enclosed 4-sided hood keeps steam and energy inside the system: energy saving up to 3 kW, less humidity in the kitchen area and better hygienic conditions
- **CLIP-IN wash and rinse arms:** wash and rinse arms can be removed with one hand and without any tools
- **Interlocked strainer:** prevents operation without tank strainer
- **EASY-CLEAN concept:** blue markings in the machine help the operator to identify the components which require cleaning
- **Thermolabel 71 °C:** default temperatures setting acc. European DIN can be switched by operator to a higher thermolabel setting
- **Watermark Approved - to WMTS-101:2018, Cert. WMKT21944**

• **NOT SUITABLE FOR CORNER INSTALLATIONS. STRAIGHT LINE / PASS THRU INSTALLATION ONLY**

*Thermostop guarantees required temperatures with cold water, the actual cycle times extend accordingly. For machine protection the water hardness should not exceed 3°dH, if higher we recommend using an integrated water softener or a HOBART HYDROLINE water treatment system.

CONNECTIONS

| | |
|-------------------------------|---------------------------------|
| ① Drain hose | 2,000 mm ID 20 / OD 25 |
| ② Supply hose | 2,000 mm R 3/4" |
| Required flow rate | 5 l/min |
| Flow pressure | 0.5 (0.8 with softener) - 6 bar |
| Max. supply water temperature | 60 °C 35 °C with RO |
| ③ Power cord | 2.500 mm |
| Supply hose for | |
| ④ Detergent | 2.000 mm |
| ⑤ Rinse aid | 2.000 mm |

DIMENSIONAL DRAWING

