

ZANUSSI PROFESSIONAL

Modular Cooking Range Line EVO700 4-Hot Plates Electric Boiling Top Range

ITEM #		
MODEL #		
NAME #		
SIS #		
AIA #		



Main Features

- Unit to be mounted on open base cupboards, bridging supports or cantilever systems.
- The four 2.6kW cast-iron plates are hermetically sealed to the one-piece top.
- The special design of the control knob system guarantees against water infiltration.
- IPX 4 water protection.

Construction

- All exterior panels in Stainless Steel with Scotch Brite finishing.
- One piece pressed 1.5 mm work top in Stainless steel.
- Model has right-angled side edges to allow flush fitting joints between units, eliminating gaps and possible dirt traps.

372015 (Z7ECEH4R00)

4-hot plate (2,6 kW each) electric boiling top

372127 (Z7ECEH4R0N)

4-hot plate (2,6 kW each) electric boiling top

Short Form Specification

Item No.

To be installed on open base installations, bridging supports or cantilever systems. Four 2.6 kW cast-iron hot plates hermetically sealed to the one-piece top. Exterior panels in stainless steel with Scotch Brite finish. One piece pressed work top in 1.5 mm thick stainless steel. Right-angled side edges to allow flush-fitting junction between units.

4-Hot	
Plates	Z
tes Electric Boil	odular
ic Boil	Cooki
ing To	ng Rai
p Ran	nge Li



Modular Cooking Range Line EVO700 4-Hot Plates Electric Boiling Top Range


Optional Accessories


Junction sealing kit	PNC 206086
• Support for bridge type installation, 800 mm	PNC 206137 □
• Support for bridge type installation, 1000 mm	PNC 206138 □
• Support for bridge type installation, 1200 mm	PNC 206139 □
• Support for bridge type installation, 1400 mm	PNC 206140 □
• Support for bridge type installation, 1600 mm	PNC 206141 □
• Frontal handrail 800 mm	PNC 206167 □
• Large handrail (portioning shelf) 800 mm	PNC 206186 □
• Frontal handrail 1200 mm	PNC 206191 □
• Frontal handrail 1600 mm	PNC 206192 □
Right and left side handrails	PNC 206240 ☐
 Water column with swivel arm (water column extension not included) 	PNC 206289 □
Water column extension	PNC 206291 □
• Chimney upstand, 800 mm	PNC 206304 □
• 2 side covering panels, height 250 mm, depth 700 mm	PNC 206320 □
• Chimney grid net, 400mm	PNC 206400 ☐






Modular Cooking Range Line EVO700 4-Hot Plates Electric Boiling Top Range





EQ = Equipotential screw



Electric

Supply voltage:

372015 (Z7ECEH4R00) 380-400 V/3 ph/50/60 Hz **372127 (Z7ECEH4R0N)** 230 V/3 ph/50/60 Hz

Total Watts: 10.4 kW

Predisposed for:

380-400V 3~ 50/60Hz

2.6 - 2.6 kW

372015 (Z7ECEH4R00) 9-10,4kW

Key Information:

372127 (Z7ECEH4RON)

Front Plates Power:

Back Plates Power:	2.6 - 2.6 kW
Front Plates dimensions:	Ø 230 Ø 230
Back Plates dimensions:	Ø 230 Ø 230
Net weight:	40 kg
Shipping weight:	
372015 (Z7ECEH4R00)	39 kg
372127 (Z7ECEH4RON)	55 kg
Shipping height:	
372015 (Z7ECEH4R00)	530 mm
372127 (Z7ECEH4RON)	540 mm
Shipping width:	820 mm
Shipping depth:	860 mm
Shipping volume:	
372015 (Z7ECEH4R00)	0.37 m ³
372127 (Z7ECEH4RON)	0.38 m ³
Certification group:	
372015 (Z7ECEH4R00)	EH74T

If appliance is set up or next to or against temperature sensitive furniture or similar, a safety gap of approximately 150 mm should be maintained or some form of heat insulation fitted.

N7CE1



Modular Cooking Range Line EVO700 4-Hot Plates Electric Boiling Top Range