

XB693

Project	
Item	
Quantity	
Date	

Model **BAKERLUX™**



- Convection oven
- Electric
- 6 trays 600x400
- Hinged left (right hand door)
- Control knob

DESCRIPTION

Combi oven with humidity, analogical control and 304 stainless steel cooking chamber. Time, temperature, steam percentage and 2 fan speeds function. Ideal for all cooking processes of fresh and frozen bakery products. The AIR.Plus multifan technology guarantees perfect cooking uniformity on all baking trays.

STANDARD COOKING FEATURES

Manual cooking

- Temperature: 80 °C 260 °C
- Convection and humidity cooking starting from 80 °C

STANDARD TECHNICAL FEATURES

- Cooking chamber in high-resistance AISI 304 stainless steel with rounded edges
- Double glass
- Cooking chamber lighting through LED lights embedded in the door
- Baking chamber with L-shaped rack rails
- Drip collection system integrated in the door and functional even with the door open
- 2-speed fan system and high-performance circular resistance

ADVANCED AND AUTOMATIC COOKING FEATURES


Unox Intensive Cooking

- DRY.Plus: extracts humidity from the cooking chamber
- STEAM.Plus: creates instant humidity starting from 48 °C
- AIR.Plus: multiple fans with reverse gear and 2 speed settings





XB693



DIMENSIONS AND WEIGHT

Width	860 mm
Depth	882 mm
Height	932 mm
Net Weight	86 kg
Pan spacing	80 mm

CONNECTION POSITIONS

2	Terminal board power supply	8	3/4" Thread water inlet	
3	Unipotential terminal	11	Cavity drain pipe	
6	Technical data plate	12	Hot fumes exhaust chimney	
7	Safety thermostat	27	Cooling air outlet	

We reserve the right to make technical improvements - 15/12/2020

POWER AND GAS SUPPLY

STANDARD

Voltage	380-415 V			
Phase	~3PH+N+PE			
Frequency	50 / 60 Hz			
Total power	10,5 kW			
Maximum Amp Draw	20 A			
Required breaker size	25 A			
Power cable requirement	H07RN-F 5G 5G			
Cord diameter	16 mm			
Plug	NOT INCLUDED			
OPTION A				
Voltage	220-240 V			
Phase	~3PH+PE			
Frequency	50 / 60 Hz			
Total power	10,5 kW			
Maximum Amp Draw	29 A			
Required breaker size	32 A			
Power cable requirement	H07RN-F 4G 4G			
Cord diameter	16 mm			
Plug	NOT INCLUDED			

ACCESSORIES

- LIEVOX: equipped with capable sensors to control and intervene automatically on the leavening process
- Neutral cabinet: recommended solution to optimize your kitchen layout and always have everything in the right place
- Stand: the ideal support to place your oven at the perfect height to work
- Baking Essentials: special trays
- SPRAY&Rinse: Practical spray detergent to manually clean all kinds of oven. Degreases and removes all kind of dirt
- PURE-RO: reverse osmosis system that eliminates Chlorides and limescale from water
- PURE: the filter reduces the carbonate hardness in water, thus avoiding scale deposits inside the oven cooking chamber

INSTALLATION REQUIREMENTS

Installations must comply with all local electrical systems, particularly as for minimum wire gauge required for field connection, hydraulic and ventilation supply. Exhaust and fume analysis must be performed in case of gas ovens.

> Register to access data and product specifications § infonet.unox.com

