



## **Technical Specifications for FVG-40**



- Easy to clean V-pan design with reduced footprint
- High performance burner and recovery rates
- Includes pilot, FFD, piezo ignitor and high temp cut-out
- 30kg/hr production rate
- 20 litre oil capacity
- Cabinet design with internal fryer controls
- Supplied with 2 fryer baskets
- Modular design
- 12 month parts and labour warranty
- Easy access for servicing





# Model Description FVG-40 2 basket sin

2 basket single pan fryer

95 MJ/h 95MJ/h

Nat Gas

LP Gas

#### V-Pan Fryer

- 95MJ/hr jet burner with pilot, FFD and piezo ignitor
- Thermostatic temperature control
- Temperature range 100 200 C
- Safety high temp cut-out
- 20 litre tank capacity
- High temp stainless steel tank
- Includes 2 stainless steel fryer baskets
- 0.9mm stainless steel perforated fish/base plate

#### **Overall Construction**

- Heavy duty construction
- Low density ceramic insulation combustion chamber
- 1.2mm 304 stainless steel front hob and splashback
- 0.9mm 304 stainless steel side panels and door
- Front and rear adjustable legs
- Rear spacer

#### **Dimensions**

- 400mm W x 800mm D (+ 35mm spacer) x 1100mm H
- Working height 900mm
- Weight 57kg
- Packed dimensions 640mm x 860mm x 1260 mm H (TBC)
- Packed weight 77kg

#### **Connections**

- Gas ¾" BSP female
- Gas 64mm from left, 212mm from floor
- In-built gas regulator (specify type of gas on order)
- Drain 1 1/4" BSP male
- Drain 200mm from left, 400mm from floor, 90mm from front

#### Cleaning & Servicing

- Easy access to all parts 7 components
- V-pan easy-to-clean design
- Rear basket support bar
- Removable baskets and inserts

### Options/Accessories

- Joining caps
- Side shields
- Additional fryer baskets
- Rear castors to replace rear legs