


16 TRAY / 2.56 M² TRAY AREA COMMERCIAL-GRADE DEHYDRATOR

COMMERCIAL USE • EASY TO MAINTAIN • FULLY STAINLESS STEEL



Uniform Drying
Without
Rotation



Completion
Cooling Cycle



Time and
Temp Memory
Function



99 Hour
Timer



Ambient - 90°C
Precision
Thermostats



Quiet
Operation



Ambient
Air Mode



Food-Grade
304 Stainless
Steel

16CUDG SPECIFICATIONS

Max Power Usage	1.5 kW	Total Tray Area	2.56 m ²
Avg Power Usage	750 W	Total Trays	16
Voltage / Frequency	220-240V/50-60Hz	Tray Dimensions	40 x 40 cm
Max Amperage	8A	Space Between Trays	35 mm
Safety Breaker Required	Single Phase/10A (Standard Household Outlet)	Tray Mesh Spacing	8 x 8 mm
Temperature Range	20°C - 90°C (1°C Increments), plus Ambient Air Mode	Machine Weight	30kg
Timer	0 - 99hr	Product Dimensions (W x H x D)	470 x 730 x 575 mm
Independent Zones	1	Average Noise Level	40 dB (Quiet)
Product Material	Food grade 304 stainless steel trays; Commercial grade stainless steel housing & latches; Aluminium door handle; Tempered glass observation window; Control Panel with PVC finish.		